



TF30



TF60R



TF18



DBZ-05

The thermostat is especially designed to protect water coils in heating or cooling systems against freezing. The entire length of the capillary tube is sensitive to temperature.

**TECHNICAL DATA**

<b>Sensitive element:</b>	gas-filled copper
<b>Switch capacity:</b>	15 (8) A 24..250Vac
<b>Contact type:</b>	SPDT micro-switch
<b>Protection:</b>	IP65, class I
<b>Size:</b>	140 x 62 x 65 mm (included cable gland)

TYPE	RANGE °C	DIFFERENTIAL K	RESET	CAPILLARY LENGTH m
<b>TF30</b>	-10...+10	2	auto	3
<b>TF30R</b>	-10...+10	FT	man	3
<b>TF60</b>	-10...+10	2	auto	6
<b>TF60R</b>	-10...+10	FT	man	6
<b>TF18</b>	-10...+10	2	auto	1.8
<b>TF18R</b>	-10...+10	FT	man	1.8

<b>ACCESSORIES</b>	DBZ-01 - Brass pocket 120mm, 12 x 1
	DBZ-02 - Stainless steel pocket AISI 304 120mm, 12 x 1
	DBZ-05 - Set of 6 mounting brackets for capillary of antifrost thermostats

**FT** manual minimal reset